

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
12 May 2005 (12.05.2005)

PCT

(10) International Publication Number  
**WO 2005/041679 A2**

(51) International Patent Classification<sup>7</sup>: A23G 3/02, 7/02

TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(21) International Application Number:

PCT/NL2004/000768

(22) International Filing Date:

3 November 2004 (03.11.2004)

(25) Filing Language:

Dutch

(26) Publication Language:

English

(30) Priority Data:

1024700 4 November 2003 (04.11.2003) NL

(71) Applicant (for all designated States except US): CFS WEERT B.V. [NL/NL]; Postbus 296, NL-6000 AG Weert (NL).

(72) Inventor; and

(75) Inventor/Applicant (for US only): ASMA, Seferinus, Jelle [NL/NL]; Van Vroonhovenlaan 1A, NL-5503 CM Veldhoven (NL).

(74) Agent: FERGUSON, Alexander; c/o Octrooibureau Vriesendorp & Gaade, P.O. Box 266, NL-2501 AW The Hague (NL).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Declaration under Rule 4.17:**

— as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

**Published:**

— without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: LOLLIPOP MACHINE

(57) Abstract: Device for manufacturing lollipops, comprising a rotatably driven drum provided with lollipop moulds at its circumference, a supply for supplying a strand of lollipop material to the lollipop moulds and a discharge for lollipops formed in the lollipop moulds, wherein the drum is disposed on a hollow shaft and wherein the lollipop moulds are disposed at the circumference of a casing, which defines an annular space with the hollow shaft, wherein the hollow shaft is provided with a first passage and a second passage, each forming a fluid connection between the cavity in the hollow shaft and the annular space, wherein the hollow shaft is provided with a fluid supply and a fluid discharge, which fluid supply is in fluid connection with a pressure source for cooling air, wherein the lollipop moulds comprise lower moulds that are fixed to the casing and the casing with the lollipop moulds forms a detachable part of the device and can be slid on the hollow shaft when being placed or removed.

WO 2005/041679 A2